

Semi-rigid Videoscope

Product Features

- 3.5" LCD display
- Support Video recording (MPEG4)
- Support Snapshot (JPEG)
- Support replay video and image
- Support reflected lens tube allow user to capture positive images when attach a mirror
- Support AV out (PAL/NTSC selectable)
- Working temperature -20° to 60° c
- Power charger indicator light
- Portable battery design allow user to charge battery at any time
- Support USB port allow user transfer data to PC
- LED illuminator light adjustable
- 2GB SD card
- Support 16 operation languages



Semi-rigid Videoscope

Display Unit	Power: DC5V Display: 3.5" TFT LCD monitor resolution: 720 x 480 Interface: USB 1.1/ 2.0, AV out Battery: Rechargeable Li-ion Battery Light adjustable knob Reset function
Camera probe (selected)	Semi-rigid OD4.3 mm Diameter/ Resolution 100,000 pixels, 60 fps@AVGA <ul style="list-style-type: none"> - Tube length: from 1-30 meter (selected) - Field of view (FOV): 67° - Depth of view (DOV): 1-2 cm to infinity - Light source: LED - Probe working Temperature: -20° to 60° C - Water/Oil proof (Ingress protection): IP57 Semi-rigid OD5.8 mm Diameter/ Resolution 300,000 pixels, 60 fps@AVGA <ul style="list-style-type: none"> - Tube length: from 1-30 meter (selected) - Field of view (FOV): 67° - Depth of view (DOV): 1-2 cm to infinity - Light source: LED - Probe working Temperature: -20° to 60° C - Water/Oil proof (Ingress protection): IP57 Semi-rigid OD8.0 mm Diameter/ Resolution 300,000 pixels, 60 fps@AVGA <ul style="list-style-type: none"> - Tube length: from 1-30 meter (selected) - Field of view (FOV): 67° - Depth of view (DOV): 1-2 cm to infinity - Light source: LED - Probe working Temperature: -20° to 60° C - Water/Oil proof (Ingress protection): IP57
Power Charger	100-240V AC in / 5.5V DC out
Option	45°-90° Side view mirror, Guide ball, AV-out cable